

## CR-M4202G Conference Microphone



The CR-M4202G conference microphone is a desktop speaking-only chairman unit. Owing to special process design, it is solid and durable. Its exquisite appearance makes it blend in with any conference rooms.

### Features

1. The chairman unit has the priority function of fully controlling the order of the conference.
2. T type connection mode is adopted and the connection position of the chairman unit is unrestricted.
3. The cardioid condenser microphone comes with a bicolor indicator. When requesting to speak, the indicator is green. It turns into red when speaking.
4. Our conference microphone is equipped with a built-in speaker, a headphone jack, and a volume control knob.
5. When the device is turned on, its built-in speaker is automatically closed. This effectively suppresses howling.

**Specification:**

<b>Model</b>	<b>CR-M4202G</b>
Power supply	Host-powered
Unit interface	Aviation 8-core dedicated interface
Maximum power consumption	3W
Headphone transmission	8-32Ω, 3.5mm mini jack
Speaker power	2W
Directional characteristic	Cardioid
Mike type	Capacitive diaphragm
Signal to noise ratio (S/N)	>80dB
Crosstalk attenuation	>80dB
Distortion	<0.1%
Frequency response	60Hz - 18KHz
Equivalent noise	≈20dB SPL
Max. SPL	105dB (3% threshold)
Sensitivity	-22Dbv/pa
Color	Black
Size (mm)	Diameter: 152 - Height: 65

**Other Option - Desktop Chairman Unit CR-M4102H**
**Specification**

<b>Model</b>	<b>CR-M4202H</b>
Power supply	Host-powered
Unit interface	Aviation 8-core dedicated interface
Maximum power consumption	1.5W
Headphone transmission	8-32Ω, 3.5mm mini jack
Speaker power	Cardioid
Directional characteristic	Capacitive diaphragm
Signal to noise ratio (S/N)	>80dB
Crosstalk attenuation	>80dB
Distortion	<0.1%
Frequency response	60Hz – 18KHz
Equivalent noise	≈20dB SPL
Max. SPL	105dB (3% threshold)
Sensitivity	-22Dbv/pa
Color	Black
Size (mm)	160Lx118Wx60H